



IMPROVED CERTIFICATIONS SEARCH TOOL. REGISTER NOW!

[LEARN MORE](#)

TGFU.R27099 Roofing Systems

[Page Bottom](#)

Roofing Systems

[See General Information for Roofing Systems](#)**SHEFFIELD METALS INTERNATIONAL**5467 EVERGREEN PKY
SHEFFIELD VILLAGE, OH 44054 USA

R27099

OTHER SYSTEMS**Class A**

1. **Deck:** C-15/32 **Incline:** Unlimited **Impact:** Class 4

Barrier Board: — 1/4 in. (min). G-P Gypsum DensDeck® or 1/4 in. (min) USG "SECUROCK® Glass Mat Roof Board" or 1/4 in (min) CertainTeed Gypsum "GlasRoc" with all joints staggered a min of 6 in. from the plywood joints.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or GCP Applied Technologies Inc. "Ice and Water Shield".

Surfacing: — Coated Steel or aluminum roofing panels, designated "SMI 1" SnapLock", "SMI 1-1/2" Mechanical Seam", "SMI 2" Mechanical Seam", "SMI 1-1/2" SnapLock 450SL", "SMI 1-1/2" SnapLock 450", "SMI 1-3/4" SnapLock", "SMI 2" A Mechanical Seam" or "SMI 1-1/2" SnapLock 550", mechanically fastened.

2. **Deck:** NC **Incline:** No Limitations **Impact:** Class 4

Barrier Board: — 1/4 in. (min). G-P Gypsum DensDeck® or 1/4 in. (min) USG "SECUROCK® Glass Mat Roof Board" or 1/4 in (min) CertainTeed Gypsum "GlasRoc".

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or GCP Applied Technologies Inc. "Ice and Water Shield".

Surfacing: — Coated Steel or aluminum roofing panels, designated "SMI 1" SnapLock", "SMI 1-1/2" Mechanical Seam", "SMI 2" Mechanical Seam", "SMI 1-1/2" SnapLock 450SL", "SMI 1-1/2" SnapLock 450", "SMI 1-3/4" SnapLock", "SMI 2" A Mechanical Seam" or "SMI 1-1/2" SnapLock 550", mechanically fastened.

3. **Deck:** NC **Incline:** No Limitations **Impact:** Class 4

Barrier Board: — 7/16 OBS or 1n% in. plywood over polyisocyanurate insulation board or polyisocyanurate composite board, any thickness.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or GCP Applied Technologies Inc. "Ice and Water Shield".

Surfacing: — Coated Steel or aluminum roofing panels, designated "SMI 1" SnapLock", "SMI 1-1/2" Mechanical Seam", "SMI 2" Mechanical Seam", "SMI 1-1/2" SnapLock 450SL", "SMI 1-1/2" SnapLock 450", "SMI 1-3/4" SnapLock", "SMI 2" A Mechanical Seam" or "SMI 1-1/2" SnapLock 550", mechanically fastened.

4. **Deck:** NC **Incline:** No Limitations **Impact:** Class 4

Barrier Board: — Polyisocyanurate, glass fiber, perlite or wood fiber, any thickness.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or GCP Applied Technologies Inc. "Ice and Water Shield".

Surfacing: — Coated Steel or aluminum roofing panels, designated "SMI 1" SnapLock", "SMI 1-1/2" Mechanical Seam", "SMI 2" Mechanical Seam", "SMI 1-1/2" SnapLock 450SL", "SMI 1-1/2" SnapLock 450", "SMI 1-3/4" SnapLock", "SMI 2" A Mechanical Seam" or "SMI 1-1/2" SnapLock 550", mechanically fastened.

5. **Deck:** NC **Incline:** No Limitations **Impact:** Class 4

Surfacing: — Coated Steel or aluminum roofing panels, designated "SMI 1" SnapLock", "SMI 1-1/2" Mechanical Seam", "SMI 2" Mechanical Seam", "SMI 1-1/2" SnapLock 450SL", "SMI 1-1/2" SnapLock 450", "SMI 1-3/4" SnapLock", "SMI 2" A Mechanical Seam" or "SMI 1-1/2" SnapLock 550", mechanically fastened.

6. **Deck:** C-15/32 **Incline:** No Limitations **Impact:** Class 4

Barrier Board: — 1/4 in. (min). G-P Gypsum DensDeck® or 1/4 in. minimum thick USG "SECUROCK® Glass Mat Roof Board" " or 1/4 in (min) CertainTeed Gypsum "GlasRoc" with all joints staggered a min of 6 in. from the plywood joints.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or GCP Applied Technologies Inc. "Ice and Water Shield".

Surfacing: — Coated Steel or aluminum roofing panels, designated "SMI 1" SnapLock", "SMI 1-1/2" Mechanical Seam", "SMI 2" Mechanical Seam", "SMI 1-1/2" SnapLock 450SL", "SMI 1-1/2" SnapLock 450", "SMI 1-3/4" SnapLock", "SMI 2" A Mechanical Seam" or "SMI 1-1/2" SnapLock 550", mechanically fastened.

Class C

1. **Deck:** C-15/32 **Incline:** Unlimited **Impact:** Class 4

Surfacing: — Coated Steel or aluminum roofing panels, designated "SMI 1" SnapLock", "SMI 1-1/2" Mechanical Seam", "SMI 2" Mechanical Seam", "SMI 1-1/2" SnapLock 450SL", "SMI 1-1/2" SnapLock 450", "SMI 1-3/4" SnapLock", "SMI 2" A Mechanical Seam" or "SMI 1-1/2" SnapLock 550", mechanically fastened.

Last Updated on 2018-03-06

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".